

**AMENDMENTS TO THE CLAIMS**

1. (Original) A method for processing image information, comprising:  
receiving light comprising image information;  
performing a first optical transform on the light to yield a first optically transformed light;  
performing a second optical transform on the light to yield a second optically transformed light;  
generating a first metric in accordance with the first optically transformed light;  
generating a second metric in accordance with the second optically transformed light;  
processing the first metric and the second metric to yield a processed metric; and  
performing an inverse optical transform on the processed metric to process the image information of the light.
2. (Original) The method of Claim 1, wherein the first optical transform is substantially similar to the second optical transform.
3. (Original) The method of Claim 1, wherein the first optical transform is compatibly different from the second optical transform.
4. (Original) The method of Claim 1, wherein:  
the first optical transform comprises a first Fourier transform; and  
the second optical transform comprises a second Fourier transform.
5. (Original) The method of Claim 1, wherein processing the first metric and the second metric to yield a processed metric comprises:  
selecting first data from the first metric;  
selecting second data from the second metric; and  
fusing the first data and the second data to yield the processed metric.

6. (Original) The metric of Claim 1, wherein processing the first metric and the second metric to yield a processed metric comprises:  
generating the processed metric in response to the first metric and the second metric; and  
detecting a target using the processed metric.
7. (Original) The method of Claim 1, further comprising:  
generating an image from the processed metric; and  
displaying the image.
8. (Original) A system for processing image information, comprising:  
a plurality of optical transformers operable to receive light comprising image information, a first optical transformer operable to perform a first optical transform on the light to yield a first optically transformed light, a second optical transformer operable to perform a second optical transform on the light to yield a second optically transformed light;  
a first processor operable to generate a first metric in accordance with the first optically transformed light;  
a second processor operable to generate a second metric in accordance with the second optically transformed light;  
an image processor operable to process the first metric and the second metric to yield a processed metric; and  
an inverse optical transformer operable to perform an inverse optical transform on the processed metric to process the image information of the light.
9. (Original) The system of Claim 8, wherein the first optical transform is substantially similar to the second optical transform.
10. (Original) The system of Claim 8, wherein the first optical transform is compatibly different from the second optical transform.

11. (Original) The system of Claim 8, wherein:  
the first optical transform comprises a first Fourier transform; and  
the second optical transform comprises a second Fourier transform.
12. (Original) The system of Claim 8, wherein the image processor is operable to process the first metric and the second metric to yield a processed metric by:  
selecting first data from the first metric;  
selecting second data from the second metric; and  
fusing the first data and the second data to yield the processed metric.
13. (Original) The system of Claim 8, wherein the image processor is operable to process the first metric and the second metric to yield a processed metric by:  
generating the processed metric in response to the first metric and the second metric; and  
detecting a target using the processed metric.
14. (Original) The system of Claim 8, further comprising a display operable to:  
generate an image from the processed metric; and  
display the image.

15. (Original) A system for processing image information, comprising:  
means for receiving light comprising image information;  
means for performing a first optical transform on the light to yield a first optically transformed light;  
means for performing a second optical transform on the light to yield a second optically transformed light;  
means for generating a first metric in accordance with the first optically transformed light;  
means for generating a second metric in accordance with the second optically transformed light;  
means for processing the first metric and the second metric to yield a processed metric;  
and  
means for performing an inverse optical transform on the processed metric to process the image information of the light.

16. (Currently Amended) A method for processing image information, comprising:

- receiving light comprising image information;
- performing a first optical transform on the light to yield a first optically transformed light, the first optical transform comprising a first Fourier transform;
- performing a second optical transform on the light to yield a second optically transformed light, the second optical transform comprising a second Fourier transform, the first optical transform substantially similar to the second optical transform or compatibly different from the second optical transform;
- generating a first metric in accordance with the first optically transformed light;
- generating a second metric in accordance with the second optically transformed light;
- processing the first metric and the second metric to yield a processed metric by performing a procedure selected from [[a]] the group consisting of a first procedure and a second procedure, the first procedure comprising: selecting first data from the first metric, selecting second data from the second metric, and fusing the first data and the second data to yield the processed metric, and second procedure comprising: generating the processed metric in response to the first metric and the second metric, and detecting a target using the processed metric;
- performing an inverse optical transform on the processed metric to process the image information of the light;
- generating an image from the processed metric; and
- displaying the image.